

APCO's OEM paragliding hardware list 2012 (6/12)






















Photo 1	CODE	Description	Photo 2
	43135	Wonder bar – Hands free two stage speed bar	
	43126	#6 Delta Maillon Stainless Steel – Diameter 6mm (not rated for minimum breaking strength)	
	34014	#4 Delta Maillon Stainless Steel – Diameter 4mm (not rated for minimum breaking strength)	
	34014p	Plastic insert for #4 Delta Maillon (34014) – Line-webbing keeper	
	34015	#4 Oval Maillon Stainless Steel for speed systems etc. – Diameter 4mm (not rated for minimum breaking strength)	
	43122	#6 Oval Maillon Stainless Steel – Diameter 6mm (not rated for minimum breaking strength)	
	43123S	#8 Oval Maillon Steel plated - Diameter 8mm (not rated for minimum breaking strength)	
	43122F	Steel Plated RAPIDE MAILLON NO:6 FOR E.P. CONNECTION Rated – MBL * 2,000kg	
	43123F	Steel plated RAPIDE MAILLON NO.8 OVAL FOR MD 28 UL BRIDLE Rated – MBL * 3,500kg	
	43126F	Delta shape rapide maillon no.6 Steel plated for PPC riser connection Rated – MBL * 1,250 kg.	
	43107A	Forged aluminum speed system pulley with brass sheave. Black annodised or polished	
	34014R	O-ring for keeping lines in place on Maillons or D-shackles	

Photo 1	CODE	Description	Photo 2
	34011	Aluminum 7075 T6 chain link [Brummel Hooks] – captive hooks for quick connection of speed system lines to risers [price per piece]	
	DCBZ-I1	Kamet cam buckle for 25mm webbing -light duty 250 Kg.	
	DCBZ-I1H	Kamet cam buckle for 25mm webbing -Heavy duty 450 Kg.	
	AP-100/2T	Aluminium forged 7075 T6 Carabiner 3 Ton 2 Twist (double safety lock) Rated - MBL* 3,000kg. Connects to 25-40mm. webbing	
	AP-100/3T	Aluminium forged 7075 T6 Carabiner 3 Ton 3 Twist (triple safety lock) Rated - MBL* 3,000kg. Connects to 25-40mm. webbing	
	34019G	Forged 7075 T6 Aluminum Press gate lock paragliding carabiner Rated - MBL* 1,800Kg Connects to 40mm. webbing	
	A4901-3T	Forged 7075 T6 Aluminium Twist Lock 3T (triple safety lock) Carabiner. Rated - MBL* 2,000kg Connects to 40mm. webbing	
	A4901L-2T	Forged 7075 T6 Aluminium Twist Lock 2T (double safetylock) Carabiner. Rated - MBL* 2,200kg Connects to 40mm. webbing	
	34019S	Stainless steel slider for quick lock buckle for 40-45mm webbing	
	34019M	Stainless steel male part for quick lock buckle for 40-45mm webbing	
	34019BD	Forged Aluminum body (female part) for quick lock buckle	

	CODE	Description	Photo 2
	S8248	Pulley Block 25mm. Stainless Steel body, plastic sheave	
	3401MT	Stainless steel T-lock male part for quick lock buckle 34019BD	
	34019MS	Stainless steel single slot male part for quick lock buckle 34019BD	
	34019MD	Stainless steel double slot male part for quick lock buckle 34019BD	
	SSL-03/28	Stainless steel male part for quick lock buckle 34019BD for 25-28mm webbing	
	SL-03/25	Stainless steel loop for 25-28mm webbing	
	SS-03/28	Stainless steel slider for 25-28mm webbing (and for QLB)	
	ASL-03/28	Aluminum 7075T6 Black Anodized male part for QLB 34019BD for 25-28mm webbing	
	AL-03/25 <i>(former AL-03/28)</i>	Aluminum 7075T6 Black Anodized loop for 25-28mm webbing	
	AS-03/28	Aluminum 7075T6 Anodized slider for QLB and light QLB 25-28mm webbing Black	
	34010	Curved safety pin for reserve parachute (Aluminium 6061-T6)	
	SSB-03I16	Stainless Steel end fitting for 40-45mm webbing	













	CODE	Description	Photo 2
	AUB03/26	Aluminum U-bracket Black Anodized. Standard height for 25mm tubing 7075 T6	
	SUB02/26	Stainless Steel U-bracket black anodized. Standard height for 25mm tubing	
	SUB02/2639	Stainless Steel U-bracket black anodized. Standard height for 25mm tubing – <i>High shoulder</i>	
	S4900-04-025/12	Rectangular loop wire welded Stainless Steel 304 for 25mm webbing	
	W900/3181F	Steel buckle loop (part of loop and slide) for 40-50mm webbing	
	W900/3181M	Steel buckle slider (part of loop and slide) for 40-50mm webbing	
	S3181D-025	Stainless Steel slider bright polished for 25mm webbing – Light Duty	
	S317-03015	3x15 round ring stainless steel welded	
	S317-03020	3x20 round ring stainless steel welded	

Photo 1	CODE	Description	Photo 2
	S317-04025	4x25 round ring stainless steel welded	
	S3250-03025	3x25 D-ring stainless steel welded	
	S3250-04025	4x25 D-ring stainless steel welded	
	A4905BD	Light QLB body (female part) Rated 1000 [Kg] MBL*	
	A4905M (Male)	Aluminium 7075T6 male part for light QLB A4905BD	
	A4905T (2 males)	Aluminium 7075T6 T-lock male part for light QLB A4905BD	
	A4903	Light QLB body (female part) Rated 800 kg. MBL*	
	A4903-I	Aluminium 7075T6 male part for light QLB A4903	
	AT4904	Aluminium 7075T6 T-lock male part for light QLB A4903	
	1234	Swivel for brake handle #8	
	1238	Neodymium Magnet 20x10x3 for brake handle and riser	
	50020	T-Bar handle reinforced plastic for brake handle	

* MBL = Minimum Breaking Load